



Multi-Charger Set for Cisco 7925G Unified Wireless IP Phone and Battery with *Dock-in-Case™* Solution

zAdapter® CI925ZDG Multi-Charger Set for Cisco 7925G Unified Wireless IP Phone and battery packs charges up to FIVE (5) 7925G handsets and FIVE (5) 7925G battery packs simultaneously.

The Multi-Charger is ideal for handsets used during consecutive, multiple shifts and keeps a fleet of phones and spare batteries charged and ready for continuous, round-the-clock use.

The unit can be placed on a desk or mounted on the wall to save space.



- The ONLY Dock-In-Case Multi-Charger for Cisco 7925G Unified Wireless IP Phone in the market
- Complete compliance with environment and safety standards
- Charge up to five (5) phones and five (5) spare batteries at the same time
- Designed with patent filed Dock-in-Case™ solution
- Charge phones while in or out of zCover carrying case
- Full access to keypad allows phone to be dialed while docked
- Easy to use, monitor phone charging process on phone screen and battery charging process with LED indicators on charger
- Battery slot has Anti-Reveres Insert Lock ensures batteries are inserted correctly, even in the dark
- Switches to a trickle charge when battery is full
- Safety first, intelligent battery temperature monitoring discontinues charge when battery temperature is over 113°F (45°C)
- Space saving design, store power supply inside Multi-Charger
- Can be placed on a desk or mounted on the wall to save space
- Power supply has switchable power cord for different countries
- Compatible with zAdapter® Voice Control Bluetooth Speaker Phone and batter

Exclusive for
Cisco 7925G Wireless IP Phone



Compatible with Cisco 7925G standard, extended battery and zBattery CI925ALT



Patent filed Dock-In-Case™ solution. Dock phone and battery in the Multi-Charger or Desktop Dual Charger with zCover case on.



Battery slots with
Anti-Reveres Insert Lock

Product ID: CI925ZDG | Compatibility: Cisco 7925G Wireless IP Phone and Battery

Specifications

Dimensions (H x W x D)	3.6in x 17.2in x 5.1in; 91mm x 437mm x 130mm
Weight	790g; 1.75lb
Power Supply	INPUT : AC100-240V 50/60Hz 1.50A OUTPUT: DC5.0V 7500mA (each slot at about 750mA)
Operating Temperature	14°F to 131°F (-10°C to 55°C)
Storage Temperature	-22°F to 140°F (-30°C to 60°C)
Relative Humidity	10 to 95% (no condensing)
Drop Specification	2.5 ft (0.75m) to concrete
Charging Time	Use zAdapter power supply: Spare battery only: 2 hours / 3 hours (standard battery pack / extended battery pack) Battery installed in phone (phone powered off): 2 hours / 3 hours (standard battery pack / extended battery pack) Battery installed in phone (powered off) and a spare battery: 2 hours / 3 hours (standard battery pack / extended battery pack)
What in the box:	1 x CI925ZDG 5 Phones / 5 Batteries Multi Charger fits Cisco 7925G Unified wireless IP phone 1 x zAdapter® Power Supply with North America AC plug for CI925ZDG 1 x User Manual 5 x Cisco 7925G IP Phone Docking CUP 1 x Wall Mount Kit

Part ID Number	Description
CI925ZDG	zAdapter CI925ZDG 5 Phones / 5 Batteries Multi Charger Set w/ AC adapter
ZDAD120A	zAdapter® AD120A power supply for Battery Multi-Charger with AC power cord, North America
ZDADAT-AU=	zAdapter® ZDACDCXA AC Power Cord, Australia
ZDADAT-JP=	zAdapter® ZDACDCXA AC Power Cord, Japan
ZDADAT-UK=	zAdapter® ZDACDCXA AC Power Cord, United Kingdom
ZDADAT-EU=	zAdapter® ZDACDCXA AC Power Cord, Continental Europe
ZDADAT-CN=	zAdapter® ZDACDCXA AC Power Cord, China

Related zCover Products



zCover, Inc.
 Tel: (604)273-3003 Fax: (604)273-3023
 PO & Sales Support: sales@zcover.com
 100-13551 Verdun Place Richmond, BC,
 Canada V6V 1W5
 Purchase Online: www.zcover.com